



STATE OF NEVADA  
DIVISION OF MINERALS  
DISSOLVED MINERAL RESOURCE EXPLORATION  
BOREHOLE OR WELL DRILLER'S PLUGGING REPORT

Report#: PB0058  
For Division Use Only

Borehole ☒  
Well ☐

PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NAC 534B

1. OPERATOR Zanskar Geothermal & Minerals, Inc.  
MAILING ADDRESS 90 S 400 W Ste 410  
Salt Lake City, UT 84101  
COUNTY Pershing

BOREHOLE OR WELL NAME: ROS-RCL-010  
PROJECT NAME: Rose of Snowville Mineral Exp.  
FEDERAL - BLM NVN# \_\_\_\_\_

2. LOCATION NW 1/4 of the NW 1/4, Sec 27 T 33 N S R 33 E  
Latitude 40.70275 or UTM E NAD83  
Longitude -118.25639 or UTM N WGS84

3. NDOM Permit/NOI Number  
NO135

4. Depth Drilled 500 Feet EXISTING BOREHOLE OR WELL CONSTRUCTION  
Depth Cased 500 Feet (well only)

5. Static water level 135 feet below land surface  
Artesian Flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature \_\_\_\_\_ °F

6. BOREHOLE/WELL PLUGGING MATERIALS  
Material Used 12 bags of From 500 feet to 20 feet ☒ Pumped ☒ Poured  
Material Used AMC Grout From \_\_\_\_\_ feet to \_\_\_\_\_ feet ☒ Pumped ☒ Poured  
Material Used 50 # From \_\_\_\_\_ feet to \_\_\_\_\_ feet ☒ Pumped ☒ Poured  
Material Used 4 bags of From 20 feet to surface feet ☒ Pumped ☒ Poured  
Material Used Cement From \_\_\_\_\_ feet to \_\_\_\_\_ feet ☒ Pumped ☒ Poured  
Material Used 94 # From \_\_\_\_\_ feet to \_\_\_\_\_ feet ☒ Pumped ☒ Poured  
Neat Cement Fluid Weight lbs/gal 15.5  
Bentonite Grout \_\_\_\_\_ % bentonite

NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR BOREHOLES SKIP TO SECTION 8

7. WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth? ☒ yes ☐ no  
If well was not cleaned out to total depth please explain why:

Was the casing pulled? ☒ yes ☐ no If pulled, from: \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Was the casing over drilled? ☒ yes ☐ no

EXISTING CASING SCHEDULE  
Material Used Size O.D. Wt/Ft Wall Thickness From To  
(Inches) (Pounds) (Inches) (Feet) (Feet)  
(Inches) (Pounds) (Inches) (Feet) (Feet)  
(Inches) (Pounds) (Inches) (Feet) (Feet)

Existing Perforations:  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet

8. Additional Notes or Comments  
Pulled NR pipe, removed plug. Trip back in. Mix and pump 500 gallons  
of grout slurry. Trip out 50 pieces of NRQ drill rod.  
Mix and pour 20' cement cap.

9. Date Started 1-29-25 Date Completed 1-29-25

10. DRILLER'S CERTIFICATION

This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Major Drilling Contractor

Address 2200 S 4000 W, Salt Lake City, UT 84120 Contractor

Phone 801-974-0645 Contractor

Nevada contractor's license number issued by the State Contractor's Board \_\_\_\_\_

Nevada driller's license number issued by the Division of Water Resources, the on-site driller \_\_\_\_\_

Signed Ryan Ricaparte by driller performing actual plugging on site

Date 1-29-25